



Features

- Ø75 - 250mm (3 - 10in) pipe
- Up to 210 m/min (700 ft/min)
- Accurate and quiet
- Intuitive HMI with setup aids
- Closed loop, variable speed adjustment
- Bell skip feature
- Remote connectivity for service support
- PSHSR Compliant
- CSA Certified

TECHNICAL SPECIFICATIONS

	6 Head Wheel Perforator				8 Head Wheel Perforator							
Technical Data	100mm 4"	150mm 6"	200mm 8"	250mm 10"	100mm 4"	150mm 6"	200mm 8"	250mm 10"				
Pipe Diameter (Single & Dual wall)	100mm 4"											
Typical Speed (ft/min)	100											
Max Operating Speed	150 ft/min											
Dimensions (L x W x H)	4.17m x 3.53m x 3.50m 164" x 139" x 138"				4.47m x 3.35m x 4.24m 176" x 132" X 174"							
Angle Between Perforations (Two offset rows)	60°				45°							
Standard Perforation Widths	0.76mm/1.52mm/2.29mm/2.79mm 0.030"/0.060"/0.090"/0.110"											
Operator Access	Left or Right of line											
Options	Cutter Wheels (Require one set per pipe size and pitch profile)				✓							
	Extra Knife Cutter Packs				✓							
	Chip Containment System				✓							